Declaration of Performance

NR: BOX / CH04 / 20150821

| 1 Product Type Store 2 Type BOX 3 Intended us of product Indoor heating 4 Manufacturer Solid fuel 7 Product Sec EN labbel Solid fuel 4 Manufacturer ARTIE ASSO KANNOUTSOS G. 8. CO O.E. 7 Address of manufacturer Prosekting Stratigous Makingioni, Evanous Thessoloniki, Greene, P.C. 56410 8 Address of autorized representative No relevance 4 Address of autorized representative No relevance 6 AVCP System 4 5 System 4 System 4 7 Harmonized technical specification EN 13 222: 2001/A2: 2004/AC: 2007 7 Harmonized technical specification EN 13 222: 2001/A2: 2004/AC: 2007 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Reaction to fire - 9 Essential characteristics Performance 9 <t< th=""><th></th><th></th><th></th></t<> | | | | |
|--|---|---|--------------------------------------|--|
| Second No. See EN label 3 Intended use of product Indoor heating Fuel Solid from Indoor heating 4 Manufacturer ARTE: ASSS KRNOUTSOS G. 8, CO O.E. Address of manufacturer Proceedus Straftigou Medigioni, Evoremos: Thesacionik, Greece, P.C: 56410 5 Authorized representative No relevance 6 AVCCP System 4 Address of authorized representative System 4 6 AVCCP System 4 Address of authorized representative No relevance 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC; 2007 8 Declared performance Reaction to fire 8 Reaction to fire - 8 Reaction to fire - 8 Reaction to fire - 9 Reaction of combustion products - 9 Reaction to fire - 9 Reaction to fire - 9 Reaction to fire - 9 CC 0.247 % | 1 | Product Type | Stove | |
| 3 Intended use of product Indoor heading 4 Vel Solid fuel 4 Address of manufacturer ARTE - ASSOS KARNOUTSOS G. & CO O.E. 5 Address of manufacturer Prosekted Straligou Madrigiani, Evesmos Thessoloniki, Greece, P.C.: 5410 5 Authorized representative No relevance 6 AVCP system(s) of assessment and verification of constancy of performance (NCP) of the construction product as set out in CPR Annex V System 4 7 Harmonized InVCP) of the construction product as set out in CPR Annex V Essential characteristics 7 Harmonized InVCP) of the construction product as set out in CPR Annex V Performance 7 Harmonized InVCP) of the construction product as set out in CPR Annex V Performance 7 Harmonized InVCP) of the construction product as set out in CPR Annex V Performance 8 Declared performance Ferformance 8 Essential characteristics Performance 8 Com 20 cm 8 Solidar 20 cm 9 Reaction to fire - 9 Cox <td< th=""><th>2</th><th>Туре</th><th>BOX</th></td<> | 2 | Туре | BOX | |
| Fuel Solid fuel 4 Monufacturer ARTE - ASSOS KARNOUTSOS G. & CO Q.E. 7 Address of manufacturer Processos Stratiguo Matrigioni. Every moss messaloniki, Greece, P.C; 54(10) 8 Address of authorized representative No relevance 6 AVCP systemily of assessment and verification of constancy of performance [AVCP] of the construction product as set out in CPR, Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Essential characteristics Performance 8 Coc 20 cm 90arc Steps 20 cm 90arc Steps 20 cm 90arc 00arc | | Serial No. | See EN label | |
| 4 Monufacturer ARIE - ASSOS KARNOUISOS G. & CO O.E. Address of manufacturer Proektasi Strafigou Makingiani, Evosmos Thessolonik, Greece, P.C.: S64100 5 Authorized representative No relevance Address of authorized representative No relevance 6 AVCP Systemily of assessment and verification of constancy of performance (AVCP) at the construction product as set out in CPR, Arrive V System 4 7 Hormonized technical specification EN 13 227: 2001/A2: 2004/AC; 2007 8 Declared performance Reaction to file 6 7 Hormonized technical specification EN 13 227: 2001/A2: 2004/AC; 2007 8 Declared performance Reaction to file 7 Min distance to combustible materials 8 Essential characteristics Performance 8 Reaction to file 9 Image: Straft S | 3 | Intended use of product | Indoor heating | |
| Address of manufacturer Proektos Stratigou Mokingioni, Evosmos Inessoliania, Greece, P.C: S410 5 Authorized representative No relevance 6 AVC F System 10 or onstancy of performance (AVCP) of the construction product as set out in CPR. Annex V System 2 7 Hormonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance 8 Essential characteristics 8 Performance 8 Essential characteristics 9 Performance 8 Essential characteristics 8 Performance 8 Essential characteristics 8 Performance 8 Essential characteristics 8 Com 8 Essential characteristics 8 Com 8 Essential characteristics 9 Performance 8 Essential characteristics 8 Performance 8 Essential characteristics 9 Rear: 20 cm Stass | | Fuel | Solid fuel | |
| Address of multiductive Thessaloniki, Greece, P.C: 5410 Authorized representative No relevance AVCP Systemi of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPA, Annex V System 4 Image: Provide technical specification EN 13 29? 2001/A2: 2004/AC: 2007 B Declared performance Essential characteristics Performance Reaction to file . Min distance to combustible materials 1 Min distance to combustible materials 8 Reaction to file . Reaction to file . Bisk of burning fuel failing out PASS Emission of combustion products . Ethousing fuel failing out PASS Ethousing face temperature . | 4 | Manufacturer | ARTE - ASSOS KARNOUTSOS G. & CO O.E. | |
| Address of authorized representative No relevance 4 AVCP System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Performance Reaction to fire - - Nin distance to combustible materials Rear 20 cm Nin distance to combustible materials Rear 20 cm Reaction to fire - - Sides: 20 cm 20 cm Front: 80 cm 80 cm Risk of burning fuel falling out PASS - Emission of combustion products - - CO 0.247 % - Dust: - - Enclosed ges moss flow: - - Exhoust ges moss flow: - - Surface temperature PASS - Exhoust ges moss flow: - - Exhoust ges moss flow: - - <th></th> <th>Address of manufacturer</th> <th></th> | | Address of manufacturer | | |
| Address of authorized representative Avec System (s) of casesment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V Hermonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 B Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials Performance Reaction to fire - Non States: Reaction to fire - | 5 | Authorized representative | No relevance | |
| System(s) of assessment and verification of construction product as set out in CPR. Annex V System 4 7 Hormonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Essential characteristics Performance 8 Reaction to fire - - 9 Coci 0.247 % - 9 Pass - <th></th> <th>Address of authorized representative</th> <th>Notelevance</th> | | Address of authorized representative | Notelevance | |
| performance (AVCP) of the construction product as set out in CPR, Amex V Iteration 7 Harmonized technical specification EN 13 229; 2001/A2: 2004/AC: 2007 8 Declared performance Reaction to fire - Min distance to combustible materials Rear: Front: 20 cm Front: 80 cm Risk of burning fuel falling out PASS Emission of combustion products - Colored - Risk of burning fuel falling out PASS Emission of combustion products - Extract gas mass flow: - Extract gas mass flow: - Extract gas mass flow: - Electrical safety - Cleanability PASS Max water operating pressure - Max water operating mersitiene (carry a chimery/flue) < | 6 | AVCP | | |
| B Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials Rear. Sides: 20 cm Front: 80 cm Risk of burning fuel folling out PASS Emission of combustion products 0.247 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhaust s lemperature: 315° C Surface temperature PASS Electrical sofety - Cleanability PASS Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output - Normal heat output: - | | performance (AVCP) of the construction product as set out in CPR, | System 4 | |
| Essential characteristics Performance Reaction to fire - Min distance to combustible materials Rear: 20 cm Sides: 20 cm Front: 80 cm Boor See installation manual Risk of burning fuel falling out PASS Emission of combustion products 0 CO: 0.247 % Dust: - OGC: - NOx: - Ethausts temperature: 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Max water operating pressure - Max mater operating pressure | 7 | Harmonized technical specification | EN 13 229: 2001/A2: 2004/AC: 2007 | |
| Essential characteristics Performance Reaction to fire - Min distance to combustible materials Rear: 20 cm Sides: 20 cm Front: 80 cm Boor See installation manual Risk of burning fuel falling out PASS Emission of combustion products 0 CO: 0.247 % Dust: - OGC: - NOx: - Ethausts temperature: 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Max water operating pressure - Max mater operating pressure | | | | |
| Reaction to fire - Min distance to combustible materials Rear: 20 cm Sides: 20 cm Front: 80 cm Risk of burning fuel falling out PASS Emission of combustion products 0.0247 % Dust: - OGC: 0.247 % Dust: - OGC: - NOx - Exhaust gas mass flow: - Exhausts temperature: 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Machanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Water heat output: - | 8 | Declared performance | | |
| Min distance to combustible materials Rear. 20 cm Sides: 20 cm Front: 80 cm Front: 90 cm Front: 90 cm Front: 90 cm Bisit: - OCC: 0.247 % Dust: - OCC: 0.247 % Dust: - OCC: - NOx: - Exhausts temperature: 315° C Surface temperature PASS Electrical sofety <th></th> <th>Essential characteristics</th> <th>Performance</th> | | Essential characteristics | Performance | |
| Rear.20 cmSides:20 cmFront:80 cmFiloor:See installation manualRisk of burning fuel falling outPASSEmission of combustion products0.247 %Dust:-OGC:0.247 %Dust:-OGC:-NOx:-Exhaust gas mass flow:-Exhaust stemperature:315° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure-Max water operating pressure-Max mater operating pressure< | | Reaction to fire | - | |
| Sides: 20 cm Front: 80 cm Floor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products 0.247 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhaust stemperature: 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Max water operating pressure - Machanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Water heat output: - Water heat output: - | | Min distance to combustible materials | | |
| Front: 80 cm Floor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products 0.247 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Electrical safety - Cleanability PASS Max water operating pressure - Max water operating pressure - Max mater operating pressure -< | | Rear: | 20 cm | |
| Floor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products O CO: 0.247 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhaust gas mass flow: - Surface temperature 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Room heat output: 6.13 kW Water heat output: - | | Sides: | 20 cm | |
| Risk of burning fuel falling out PASS Emission of combustion products CO: 0.247 % Dust: - OGC: OGC: - NOx: NOx: - - Exhaust gas mass flow: - - Max det emperature PASS - Max water operating pressure - - Mechanical resistance (carry a chimney/flue) PASS - Thermal output 6.13 kW - Room heat output: - - Mater head output: - - | | Front: | 80 cm | |
| Emission of combustion products CO: 0.247 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhausts temperature: 315° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Room heat output: - Water heat output: - | | Floor: | See installation manual | |
| CO:0.247 %Dust:-OGC:-NOx:-NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhaust stemperature:315° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output:6.13 kWRoom heat output:6.13 kWWater heat output:- | | Risk of burning fuel falling out | PASS | |
| Dust:-OGC:-NOx:-NOx:-Exhaust gas mass flow:-Exhausts temperature:315° CSurface temperature9ASSElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output6.13 kWRoom heat output:6.13 kWWater heat output:-Vater heat output:- | | Emission of combustion products | | |
| OGC:.NOx:.Exhaust gas mass flow:.Exhaust gas mass flow:.Exhausts temperature:315° CSurface temperaturePASSElectrical safety.CleanabilityPASSMax water operating pressure.Mechanical resistance (carry a chimney/flue)PASSThermal output.Normal heat output:6.13 kWRoom heat output:6.13 kWWater heat output:. | | CO: | 0.247 % | |
| NOx: Exhaust gas mass flow: Exhausts temperature:-Exhausts temperature:315° CSurface temperature315° CElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output6.13 kWRoom heat output: Water heat output:6.13 kWWater heat output:- | | Dust: | - | |
| Exhaust gas mass flow: Exhausts temperature:-Surface temperature315° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output6.13 kWRoom heat output: Water heat output:6.13 kWWater heat output:- | | OGC: | - | |
| Exhausts temperature:315° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output6.13 kWRoom heat output:6.13 kWWater heat output:6.13 kW | | NOx: | - | |
| Surface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure-Mechanical resistance (carry a chimney/flue)PASSThermal output6.13 kWRoom heat output:6.13 kWWater heat output:-Vater heat output:- | | Exhaust gas mass flow: | - | |
| Electrical safety - Cleanability PASS Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output 0.13 kW Room heat output: 0.13 kW Water heat output: 0.13 kW | | Exhausts temperature: | 315° C | |
| Cleanability PASS Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output 0.13 kW Normal heat output: 0.13 kW Water heat output: 0.13 kW Water heat output: 0.13 kW | | Surface temperature | PASS | |
| Max water operating pressure - Mechanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Normal heat output: 6.13 kW Room heat output: 6.13 kW Water heat output: - | | Electrical safety | - | |
| Mechanical resistance (carry a chimney/flue) PASS Thermal output 6.13 kW Normal heat output: 6.13 kW Room heat output: 6.13 kW Water heat output: - | | Cleanability | PASS | |
| Thermal output Normal heat output: 6.13 kW Room heat output: 6.13 kW Water heat output: - | | Max water operating pressure | - | |
| Normal heat output: 6.13 kW Room heat output: 6.13 kW Water heat output: - | | Mechanical resistance (carry a chimney/flue) | PASS | |
| Room heat output: 6.13 kW Water heat output: - | | Thermal output | | |
| Water heat output: - | ſ | Normal heat output: | 6.13 kW | |
| | | Room heat output: | 6.13 kW | |
| Energy efficiency 70.5 % | | Water heat output: | - | |
| | | Energy efficiency | 70.5 % | |

Declaration:

The performance of the product identified in points 1 & 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Georgios Karnoutsos, CEO af h (Signature)

Thessaloniki, 21/08/2015