Declaration of Performance

NR: MENTOR ST 80 Hydro / MNS80 / 20181010

1	Product Type	Fireplace
2	Туре	MENTOR ST 80 Hydro
	Serial No.	See EN label
3	Intended use of product	Indoor heating
	Fuel	Solid fuel
4	Manufacturer	ARTE - ASSOS KARNOUTSOS G. & CO O.E.
	Address of manufacturer	Proektasi Stratigou Makrigiani, Evosmos Thessaloniki, Greece, P.C: 56410
5	Authorized representative	
	Address of authorized representative	-
6	AVCP	
	System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	System 4
7	Harmonized technical specification	EN 13 229: 2001/A2: 2004/AC: 2007

8	Declared performance		
	Essential characteristics	Performance	
	Reaction to fire	-	
	Min distance to combustible materials		
	Rear:	10 cm	
	Sides:	10 cm	
	Front:	80 cm	
	Floor:	See installation manual	
	Risk of burning fuel falling out	PASS	
	Emission of combustion products		
	CO:	0.088 %	
	Dust:	-	
	OGC:	-	
	NOx:	-	
	Exhaust gas mass flow:	-	
	Exhausts temperature:	227° C	
	Surface temperature	PASS	
	Electrical safety	PASS	
	Cleanability	PASS	
	Max water operating pressure	2.5 bar	
	Mechanical resistance (carry a chimney/flue)	PASS	
	Thermal output		
	Normal heat output:	24.03 KW	
	Room heat output:	6.96 KW	
	Water heat output:	17.07 KW	
	Energy efficiency	84.29 %	

Declaration:

The performance of the product identified in points 1 & 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Thessaloniki, 10/10/2018

Georgios Karnoytsos, CEO

(Signature)