Declaration of Performance

NR: PHOENIX HYDRO OVEN / PH47-HY10-OV35 / 20150821

1 Product Type Stove 2 Type PHOLENK HYDRO OVEN 3 Intended use of product Indoor heating 6 Fuel Selicit fuel 7 Fuel Selicit fuel 6 Autorized representative Product Stratigou Makrigiani, Evormos Thestalioniki, Greece, P.C; 5410 7 Autorized representative No relevance 4 AvCP System 4 7 Hormonized technical specification Entrastalioniki, Greece, P.C; 5410 7 Hormonized technical specification System 4 7 Hormonized technical specification Entrastalioniki, Greece, P.C; 5410 7 Hormonized technical specification Entrastalioniki, Greece, P.C; 5410 7 Hormonized technical specification Entrastalioniki, Greece, P.C; 5410 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Essential characteristics			
Second No. See EN label 3 Intended use of product Indoor heating 4 Manufacturer Solid fuel 4 Manufacturer Proektos Strafigou Mokidgini, Evosmos Thessaloniki, Greece, P.C: 5410 5 Authotized representative No relevance 4 Address of authotized representative No relevance 6 AVCP System fol of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR. Annex V System 4 7 Hormonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Performance 8 Essential characteristics Performance 8 Essential characteristics Performance 8 Cor 25 cm 9 Rearr 25 cm 9 Rearr 0 cm 10:or See installation manual 10:or See installation manual 10:or Emast set outs temperature: 10:or Cor 0.140 % 10:or Emast semoust temperature:	1	Product Type	Stove
3 Intended use of product Indoor heating. 4 Manufacturer Solid fuel 4 Address of manufacturer Proektad Stratigou Makingiani, Evosmos Thessaloniki, Greece, P.C: \$6410 5 Authorized representative No relevance 6 AVCP System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V System 4 7 Hormonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Feaction to fire - Min distance to combustible materials Rear: Sides: 1 Rear: Front: 25 cm 5 Bisk of burning fuel failing out PASS Exist of combustible products - 0 CO: Nobic 0.140 %. 0 Dust: Exhaust firemperature: - 1000rt Exist of burning fuel failing out PASS Extra of combustion products - - 0 CO: Nobic - Extra of combustion products - Extreal of combustion products -	2	Туре	PHOENIX HYDRO OVEN
Fuel Solid fuel 4 Manufacturer ARTE - ASSOS KARNOUTSOS G. & CO.O.E. Address of annufacturer Proektas Stratingou Makrigiani. Evosmos Thessaloniki, Greace, P.C. 50410 5 Authorized representative No relevance 6 AVCP System A 6 AVCP System 4 Annex V EN 13 229: 2001/A2: 2004/AC: 2007 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials Sides: Reaction to fire - Reaction to fire		Serial No.	See EN label
4 Manufacturer ARTE - ASSOS KARNOUTSOS G. & CO O.E. Address of manufacturer Provektod Stratigou Makrigiani, Evosmos Thessalaniki, Greece, P.C: 56410 5 Authorized representative No relevance 4 Address of authorized representative No relevance 6 AVCP System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Reaction to fire - Nin distance to combustible materials Performance Reaction to fire - 8 Rear 25 cm 8 Rear 25 cm 9 State of burning fuel falling out PASS 9 Co 0.140 % 9 Co - 9 Surface temperature 191° C 9 Surface temperature PASS 9 Exhaust stemperature 191° C 9 Cleanability -	3	Intended use of product	Indoor heating
Address of manufacturer Proektail Stratigou Mokrigioni, Evosmos Thessoloniki, Greece, P.C: 56410 5 Authorized representative No relevance 6 AVCP No relevance 5 Authorized representative System 4 6 AVCP System 50 of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR. Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Fescation to file - Min distance to combustible materials Performance Reaction to file - Risk of burning fuel falling out Rear: Risk of burning fuel falling out PASS Emission of combustion products - Coc 0.140 % Duck - Active temperature 1919 °C Surface temperature Exhaust temperature Exhaust temperature PASS Exhaust temperature PASS Exhaust temperature PASS Exhaust temperature PASS <tr< th=""><th></th><th>Fuel</th><th>Solid fuel</th></tr<>		Fuel	Solid fuel
Address of manuacturer Thessoloniki. Greece, P.C: 56410 Address of authorized representative No relevance Address of authorized representative No relevance Address of authorized representative System (s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR. Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Essential characteristics Performance Reaction to fire - - Min distance to combustible materials Nore Sides: 25 cm - Front: 80 cm 80 cm - Risk of burning fuel failing out PASS - - Co: 0.140 % - - Autor centeration - - - Basison of combustion products - - - Entission of combustion products - - - Exhoust gas mass flow: - - - Exhoust grammas flow: - - - <tr< th=""><th>4</th><th>Manufacturer</th><th>ARTE - ASSOS KARNOUTSOS G. & CO O.E.</th></tr<>	4	Manufacturer	ARTE - ASSOS KARNOUTSOS G. & CO O.E.
Address of authorized representative No relevance 6 AVCP System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials Rear: Reaction to fire - No relevance Boom Biology 25 cm Front: 80 cm Risk of burning fuel falling out PASS Emission of combustion products - CO: 0.140 % Dust: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhaust stemperature 1919 °C Surface temperature PASS Electrical solety - Cleanability PASS Max water operating pressure 2.5 bar		Address of manufacturer	
Address of authorized representative 6 AVCP System(i) of assessment and veilification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V System 4 7 Harmonized technical specification EN 13 229; 2001/A2; 2004/AC; 2007 8 Declared performance 8 Reaction to fire 6 Sesential characteristics 8 Reaction to fire 9 Image: Performance 8 Reaction to fire 9 Performance 9 Reaction to fire 9 Reaction to fire 10 10 10 10 11 25 cm 11 80 cm 11 80 cm 11 80 cm 11 100 11 80 cm 11 100 11 100 12 100 13 100 13 100 14 100 15 10 16 10 17 10 18 10 10 00 10 00 10 10 10 10 10 10	5	Authorized representative	No rolovanco
System(s) of assessment and vetification of constancy of performance (AVCP) of the construction product as set our in CPR Annex V System 4 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Reaction to fire - Min distance to combustible materials Rear: Reaction to fire - Nin distance to combustible materials Rear: Reaction to fire - Risk of burning fuel falling out Co		Address of authorized representative	NUTEIEVUTICE
performance (AVCP) of the construction product as set out in CPR. Annex V Image: Construction product as set out in CPR. Annex V 7 Harmonized technical specification EN 13 229: 2001/A2: 2004/AC: 2007 8 Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials - Rear: 25 cm Sides: 25 cm Biologic 25 cm Front: 80 cm Homonized technical specification 80 cm Risk of burning fuel falling out PASS Emission of combustion products - CO: 0.140 % Dust: - OGC: - NOx: - Exhaust gas mass flow:	6	AVCP	
B Declared performance Essential characteristics Performance Reaction to fire - Min distance to combustible materials Rear: 25 cm Sides: 25 cm Front: 80 cm Roor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products CO: 0.140 % Dust: - - OGC: - - Nox: - - Exhaust gas mass flow: - - Exhaust stemperature: 191° C - Surface temperature PASS - Electrical safety - - Cleanability PASS - Max water operating pressure 2.5 bar - Mechanical resistance (carry a chimney/flue) PASS -		performance (AVCP) of the construction product as set out in CPR,	System 4
Essential characteristics Performance Reaction to fire - Min distance to combustible materials - Rear: 25 cm Sides: 25 cm Front: 80 cm Floor: See installation manual Rtsk of burning fuel falling out PASS Emission of combustion products - OGC: - NOx: - Exhaust gas mass flow: - Exhaust stemperature: 191° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure 2.5 bar Mechanical resistance (carry a chimney/flue) PASS	7	Harmonized technical specification	EN 13 229: 2001/A2: 2004/AC: 2007
Essential characteristics Performance Reaction to fire - Min distance to combustible materials - Rear: 25 cm Sides: 25 cm Front: 80 cm Floor: See installation manual Rtsk of burning fuel falling out PASS Emission of combustion products - OGC: - NOx: - Exhaust gas mass flow: - Exhaust stemperature: 191° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure 2.5 bar Mechanical resistance (carry a chimney/flue) PASS	_		
Reaction to fire - Min distance to combustible materials Rear: 25 cm Reaction to fire 25 cm Sides: 25 cm Bits 80 cm Front: 80 cm Floor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products 000000000000000000000000000000000000	8	Declared pe	rformance
Min distance to combustible materials Rear: 25 cm Sides: 25 cm Front: 80 cm Front: 80 cm Floor: See installation manual Risk of burning fuel falling out PASS Emission of combustion products 0.140 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas m		Essential characteristics	Performance
Rear:25 cmSides:25 cmFront:80 cmFloor:See installation manualRisk of burning fuel falling outPASSEmission of combustion products0.140 %Dust:-OGC:0.140 %N0x:-Exhaust gas mass flow:-Exhausts temperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMack mater a chimney/flue)PASS		Reaction to fire	-
Sides:25 cmFront:80 cmFloor:See installation manualRisk of burning fuel falling outPASSEmission of combustion products0.140 %Dust:-OGC:0.140 %N0x:-Khaust gas mass flow:-Exhausts temperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chinney/flue)PASS		Min distance to combustible materials	
Front:80 cmFloor:See installation manualRisk of burning fuel falling outPASSEmission of combustion productsCO:CO:0.140 %Dust:-OGC:-NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhaust stemperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Rear:	25 cm
Floor:See installation manualRisk of burning fuel falling outPASSEmission of combustion productsCO:0.140 %Dust:-OGC:-NOx:-Exhaust gas mass flow:-Exhaust stemperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Sides:	25 cm
Risk of burning fuel falling out PASS Emission of combustion products CO: 0.140 % Co: 0.140 % Dust: - OGC: - NOx: - Exhaust gas mass flow: - Exhaust gas mass flow: - Exhaust stemperature: 191° C Surface temperature PASS Electrical safety - Cleanability PASS Max water operating pressure 2.5 bar Mechanical resistance (carry a chimney/flue) PASS		Front:	80 cm
Emission of combustion productsCO:0.140 %Dust:-OGC:-NOx:-Exhaust gas mass flow:-Exhausts temperature:191° CSurface temperature191° CSurface temperature-Electrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Floor:	See installation manual
CO:0.140 %Dust:-OGC:-NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhaust stemperature:191° CSurface temperature191° CElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Risk of burning fuel falling out	PASS
Dust:-OGC:-NOx:-NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhaust stemperature:191° CSurface temperature191° CElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Emission of combustion products	
OGC:-NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhausts temperature:191° CSurface temperature191° CElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		CO:	0.140 %
NOx:-Exhaust gas mass flow:-Exhaust gas mass flow:-Exhausts temperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Dust:	-
Exhaust gas mass flow: Exhausts temperature:-Surface temperature191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		OGC:	-
Exhausts temperature:191° CSurface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		NOx:	-
Surface temperaturePASSElectrical safety-CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Exhaust gas mass flow:	-
Electrical safety - Cleanability PASS Max water operating pressure 2.5 bar Mechanical resistance (carry a chimney/flue) PASS		Exhausts temperature:	191° C
CleanabilityPASSMax water operating pressure2.5 barMechanical resistance (carry a chimney/flue)PASS		Surface temperature	PASS
Max water operating pressure 2.5 bar Mechanical resistance (carry a chimney/flue) PASS		Electrical safety	-
Mechanical resistance (carry a chimney/flue) PASS		Cleanability	PASS
		Max water operating pressure	2.5 bar
·		Mechanical resistance (carry a chimney/flue)	PASS
Thermal output		Thermal output	
Normal heat output: 16.18 kW		Normal heat output:	16.18 kW
Room heat output: 7.99 kW		Room heat output:	7.99 kW
Water heat output: 8.19 kW		Water heat output:	8.19 kW
		Energy efficiency	82.55 %
		Energy efficiency	82.55 %

Declaration:

The performance of the product identified in points 1 & 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Georgios Karnoutsos, CEO af (Signature)

Thessaloniki, 21/08/2015