Declaration of Performance

NR: SOL 90 / CAS90 / 20150713

1	Product Type	Insert
2	Туре	SOL 90
	Serial No.	See EN label
3	Intended use of product	Indoor heating
	Fuel	Solid fuel
4	Manufacturer	ARTE - ASSOS KARNOUTSOS G. & CO O.E.
	Address of manufacturer	Proektasi Stratigou Makrigiani, Evosmos Thessaloniki, Greece, P.C: 56410
5	Authorized representative	No relevance
	Address of authorized representative	
6	AVCP	System 3
	System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	Reihn-Ruhr Feuerstatten Prufstelle, NB:1625 RRF - 29 16 4377 / 13.07.2015
7	Harmonized technical specification	EN 13 229: 2001/A2: 2004/AC: 2007

Declared performance		
Essential characteristics	Performance	
Reaction to fire	-	
Min distance to combustible materials		
Rear:	10 cm	
Sides:	10 cm	
Front:	120 cm	
Floor:	See installation manual	
Risk of burning fuel falling out	PASS	
Emission of combustion products		
CO:	1125 mg/m³ [0.09%]	
Dust:	22 mg/m³	
OGC:	89 mg/m³	
NOx:	137 mg/m³	
Exhaust gas mass flow:	16.3 g/s	
Exhausts temperature:	269° C	
Surface temperature	PASS	
Electrical safety	PASS	
Cleanability	PASS	
Max water operating pressure	-	
Mechanical resistance (carry a chimney/flue)	PASS	
Thermal output	•	
Normal heat output:	16 kW	
Room heat output:	16 kW	
Water heat output:	-	
Energy efficiency	77 %	

Declaration:

The performance of the product identified in points 1 & 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Thessaloniki, 13/07/2015

Georgios Karnoutsos, CEO